

# SELENIA TURBO DIESEL 10W-40

## DESCRIPTION

Synthetic based motor oil for diesel cars equipped turbo-charged or multi-valve indirect or direct injection engines. Also ideal for aspirated diesel cars.

SELENIA TURBO DIESEL is specifically formulated to prevent the thickening caused by the carbon residues of combustion products, common in indirect injection engines with pre-combustion chambers.

## CHARACTERISTICS


SELENIA TURBO DIESEL offers all the distinctive characteristics of the oils in the Selenia range, which include: lower oil consumption, cleaner engines and maximum stability at high temperatures. It also guarantees:

**Improved cold starting as a result of the high fluidity;**

**Excellent resistance to high temperatures;**

**Optimal dispersion of engine protection additives.**

In the turbo charged engines, it eliminates the risk of piston rings sticking and the consequent engine seizing, due to the combined effect of high temperature and pressure.



## ADVICE ON USE

Changes should be as indicated by Fiat.

Oil changes are advised up to 20,000 km on cars with direct injection engines and up to 10,000 km on cars with indirect injection engines.

## RECOMMENDED BY

Fiat, Lancia, Alfa Romeo, Innocenti.

## TECHNICAL DATA

SAE 10W-40, ACEA B3, API CD/SF, CCMC PD2, VW 505.00, MIL-L-2104D LEVEL, FIAT 9.55535

